

Mounted

MODEL		litres	Two Bin		Three Bin
			3000	4000	4500
-bin splits			1500/1500	2000/2000	1500/1500/1500
CAPACITY:					
-all wheat	(x 0.78)	(kg)	2340	3120	3510
-all fertiliser	(x 1.0)	(kg)	1500	4000	4500
-wheat/fertiliser		(kg)	1170/1500	1560/2000	n/a
-wheat/fertiliser/urea	(x 0.76)	(kg)	n/a	n/a	1170/1500/1140
SMALL SEEDS BOX OPTION					
		(litres)	280	280	280
METERING OUTLETS PER BIN:					
- Single Shoot	No. x diam(mm)		6 x 64	6 x 64	6 x 64
- Double Shoot	No. x diam(mm)		3 x 64	3 x 64	3 x 64
NO. OF SOWING OUTLETS:					
- Single Shoot	- min		15	15	15
	- max		66	66	66
- Double Shoot	- min		2 x 15	2 x 15	2 x 15
	- max		2 x 66	2 x 66	2 x 66
DIMENSIONS:					
- Ground Clearance		(m)	n/a	n/a	n/a
- Length		(m)	3.10	3.34	4.20
- Width		(m)	2.25	2.38	2.25
- Height (to fill)		(m)	2.75	2.80	2.75
WEIGHT EMPTY (APPROX)					
		(kg)	1200	1300	1800
TYRES:					
- Front			n/a	n/a	n/a
- Rear			n/a	n/a	n/a
WHEEL TRACK					
- front		(m)	n/a	n/a	n/a
- rear		(m)	n/a	n/a	n/a



METERING DRIVE SYSTEM	Electric variable drive or ground driven spur gear
MATERIAL SOWING CAPACITY	Up to 5 tonnes per hour maximum sowing capacity - depending on model
PRIMARY HOSE DIAMETER	64 mm
DISTRIBUTION HEADS:	
- Single (64 mm inlet)	5, 6, 7, 8, 9, 10 & 11 outlets - 32 mm or 38 mm diameter
- Single (44.5 mm inlet)	5, 6, 7, 8, 9, 10 & 11 outlets - 32 mm or 38 mm diameter
OPTIONAL EQUIPMENT:	
	Hose, head and boot kits to suit most cultivators.
	Small Seeds Box.
	Liquid Tank (on 3 bin models only).
	Rear mounted tow bar for towing harrows or prickle chains.
	Loading auger (200 mm diameter).
	Wing Cut-Off (allows seeding to occur only through the centre frame).
	Load Cells (to measure inputs of bin contents accurately).
	Work Light Kit.