

## Tow Behind (Quad Wheeled)

			Two Bin				Three Bin								
MODEL		litres	4000	6000	8000	10000	12000	14000	4500	7000	9000	11000	13000	15000	
-bin splits			2000/2000	2600/3400	3580/4750	4500/5800	5400/6700	6100/7900	3 x 1500	3 x variable	3 x variable	3 x variable	3 x variable	3 x variable	
<b>CAPACITY:</b>															
-all wheat	(x 0.78)	(kg)	3120	4680	6500	8030	9440	10920	3510	5600	7070	8775	10140	11895	
-all fertiliser	(x 1.0)	(kg)	4000	6000	8330	10300	12100	14000	4500	7170	9060	11250	13250	15250	
-wheat/fertiliser		(kg)	1560/2000	2030/3400	2790/4750	3510/5800	4210/5090	4760/6000	n/a	n/a	n/a	n/a	n/a	n/a	
-wheat/fertiliser/urea	(x 0.76)	(kg)	n/a	n/a	n/a	n/a	n/a	n/a	1170/1500/1140	variable	variable	variable	variable	variable	
<b>SMALL SEEDS BOX OPTION</b>			(litres)	280	520	600	600	600	600	600	600	600	600	600	
<b>METERING OUTLETS PER BIN:</b>															
- Single Shoot	No. x diam(mm)		6 x 64	8 x 64	12 x 64	12 x 64	12 x 64	12 x 64	6 x 64	8 x 64	12 x 64	12 x 64	12 x 64	12 x 64	
- Double Shoot	No. x diam(mm)		3 x 64	4 x 64	6 x 64	6 x 64	6 x 64	6 x 64	3 x 64	4 x 64	6 x 64	6 x 64	6 x 64	6 x 64	
<b>NO. OF SOWING OUTLETS:</b>															
- Single Shoot	- min		15	20	30	30	30	30	15	20	30	30	30	30	
	- max		66	88	132	132	132	132	66	88	132	132	132	132	
- Double Shoot	- min		2 x 15	2 x 20	2 x 30	2 x 30	2 x 30	2 x 30	2 x 15	2 x 20	2 x 30	2 x 30	3 x 30	2 x 30	
	- max		2 x 66	2 x 88	2 x 132	2 x 132	2 x 132	2 x 132	2 x 66	2 x 88	2 x 132	2 x 132	3 x 132	2 x 132	
<b>DIMENSIONS:</b>															
- Ground Clearance	(m)		0.50	0.45/0.57	0.63	0.73	0.55	0.55	0.40	0.45/0.57	0.63	0.73	0.55	0.55	
- Length	(m)		7.13	8.88	9.40	9.90	9.90	9.90	8.10	8.88	9.40	9.90	8.01	9.90	
- Width	(m)		2.75	3.23	3.87	3.87	4.25 - 4.92	4.25 - 4.92	2.73	3.23	3.87	3.87	4.25 - 4.92	4.25 - 4.92	
- Height (to fill)	(m)		2.62	2.75/2.87	2.98	3.08	2.98	3.17	2.36	2.62/2.74	2.98	3.08	3.08	3.14	
<b>WEIGHT EMPTY (APPROX)</b>			(kg)	2375	3150	5250	5700	5800	5900	2875	3350	5500	5950	6150	6200
<b>TYRES:</b>															
- Front			15.5/80 x 24	18.4 x 30	18.4 x 30	18.4 x 30	30.5 x 32	30.5 x 32	18.4 x 30	18.4 x 30	18.4 x 30	18.4 x 30	30.5 x 32	30.5 x 32	
- Rear			15.5/80 x 24	18.4 x 30	30.5 x 32	30.5 x 32	18.4 x 30 (opt)	30.5 x 32	18.4 x 30	18.4 x 30	30.5 x 32	30.5 x 32	30.5 x 32	30.5 x 32	
				18.4 x 30 (opt)											
<b>WHEEL TRACK</b>															
- front	(m)		2.00 - 2.20	2.05	3.00	3.00	2.80 - 3.40	2.80 - 3.40	2.05	2.05	3.00	2.59 - 3.30	2.80 - 3.40	2.80 - 3.40	
- rear	(m)		2.00 - 2.20	2.55/2.0	3.00	3.00	3.40 - 4.16	3.40 - 4.16	2.00	2.55/2.0	3.00	3.40 - 4.16	3.40 - 4.16	3.40 - 4.16	
			2.00 (opt)	2.00 (opt)					2.00 (opt)						

<b>METERING DRIVE SYSTEM</b>	Electric variable drive or ground driven spur gear
<b>MATERIAL SOWING CAPACITY</b>	Up to 5 tonnes per hour maximum sowing capacity - depending on model
<b>PRIMARY HOSE DIAMETER</b>	64 mm
<b>DISTRIBUTION HEADS:</b>	
- Single (64 mm inlet)	5, 6, 7, 8, 9, 10 & 11 outlets - 32 mm or 38 mm diameter
- Single (44.5 mm inlet)	5, 6, 7, 8, 9, 10 & 11 outlets - 32 mm or 38 mm diameter
<b>OPTIONAL EQUIPMENT:</b>	
	Hose, head and boot kits to suit most cultivators.
	Small Seeds Box.
	Liquid Tank (on 3 bin models only).
	Rear mounted tow bar for towing harrows or prickle chains.
	Loading auger (200 mm diameter).
	Wing Cut-Off (allows seeding to occur only through the centre frame).
	Load Cells (to measure inputs of bin contents accurately).
	Work Light Kit.

