

Tow Behind (Trike Style)

| | | | Two Bin | | | | | Three Bin | | | |
|----------------------------------|----------------|------|--------------|--------------|--------------|--------------|----------------|--------------------|--------------|--------------|--------------|
| MODEL | | | 4000 | 6000 | 8000 | 10000 | 4500 | 6000 | 7000 | 9000 | 11000 |
| -bin splits | litres | | 2000/2000 | 2600/3400 | 3580/4750 | 4500/5800 | 3 x 1500 | 3 x 2000 | 3 x variable | 3 x variable | 3 x variable |
| CAPACITY: | | | | | | | | | | | |
| -all wheat | (x 0.78) | (kg) | 3120 | 4680 | 6500 | 8030 | 3510 | 4680 | 5600 | 7070 | 8775 |
| -all fertiliser | (x 1.0) | (kg) | 4000 | 6000 | 8330 | 10300 | 4500 | 6000 | 7170 | 9060 | 11250 |
| -wheat/fertiliser | | (kg) | 1560/2000 | 2030/3400 | 2790/4750 | 3510/5800 | n/a | n/a | n/a | n/a | n/a |
| -wheat/fertiliser/urea | (x 0.76) | (kg) | n/a | n/a | n/a | n/a | 1170/1500/1140 | 1560/2000/1520 | variable | variable | variable |
| SMALL SEEDS BOX OPTION | (litres) | | 280 | 520 | 600 | 600 | 280 | 280 | 520 | 600 | 600 |
| METERING OUTLETS PER BIN: | | | | | | | | | | | |
| - Single Shoot | No. x diam(mm) | | 6 x 64 | 8 x 64 | 12 x 64 | 12 x 64 | 6 x 64 | 6 x 64 | 8 x 64 | 12 x 64 | 12 x 64 |
| - Double Shoot | No. x diam(mm) | | 3 x 64 | 4 x 64 | 6 x 64 | 6 x 64 | 3 x 64 | 3 x 64 | 4 x 64 | 6 x 64 | 6 x 64 |
| NO. OF SOWING OUTLETS: | | | | | | | | | | | |
| - Single Shoot | - min | | 15 | 20 | 30 | 30 | 15 | 15 | 20 | 30 | 30 |
| | - max | | 66 | 88 | 132 | 132 | 66 | 66 | 88 | 132 | 132 |
| - Double Shoot | - min | | 2 x 15 | 2 x 20 | 2 x 30 | 2 x 30 | 2 x 15 | 2 x 15 | 2 x 20 | 2 x 30 | 2 x 30 |
| | - max | | 2 x 66 | 2 x 88 | 2 x 132 | 2 x 132 | 2 x 66 | 2 x 66 | 2 x 88 | 2 x 132 | 2 x 132 |
| DIMENSIONS: | | | | | | | | | | | |
| - Ground Clearance | (m) | | 0.45 | 0.40 | 0.50 | 0.40 | 0.40 | 0.40 | 0.40 | 0.50 | 0.40 |
| - Length | (m) | | 4.80 | 5.70 | 6.65 | 7.10 | 5.80 | 6.60 | 6.10 | 6.65 | 7.10 |
| - Width | (m) | | 2.75 | 2.95 | 3.92 | 4.10 | 2.47 | 2.79 | 3.20 | 3.92 | 4.10 |
| - Height (to fill) | (m) | | 2.57 | 2.70 | 2.65 | 2.67 | 2.36 | 2.52 | 2.60 | 2.65 | 2.67 |
| WEIGHT EMPTY (APPROX) | (kg) | | 1700 | 2250 | 3600 | 3900 | 2150 | 2200 | 2950 | 3750 | 4050 |
| TYRES: | | | | | | | | | | | |
| - Front | | | 10.5/80 x 18 | 10.5/80 x 18 | 15.5/80 x 24 | 15.5/80 x 24 | 10.5/80 x 18 | 10.5/80 x 18 | 15.5/80 x 24 | 15.5/80 x 24 | 15.5/80 x 24 |
| - Rear | | | | | | | | 15.5/80 x 24 (opt) | | | |
| WHEEL TRACK | | | | | | | | | | | |
| - front | (m) | | 18.4 x 30 | 18.4 x 30 | 30.5 x 32 | 30.5 x 32 | 18.4 x 30 | 18.4 x 30 | 30.5 x 32 | 30.5 x 32 | 30.5 x 32 |
| - rear | (m) | | 0.39 | 0.39 | 0.48 | 0.48 | 0.39 | 0.39 | 0.48 | 0.48 | 0.48 |



| | |
|---------------------------------|---|
| METERING DRIVE SYSTEM | Electric variable drive or ground driven spur gear |
| MATERIAL SOWING CAPACITY | Up to 5 tonnes per hour maximum sowing capacity - depending on model |
| PRIMARY HOSE DIAMETER | 64 mm |
| DISTRIBUTION HEADS: | |
| - Single (64 mm inlet) | 5, 6, 7, 8, 9, 10 & 11 outlets - 32 mm or 38 mm diameter |
| - Single (44.5 mm inlet) | 5, 6, 7, 8, 9, 10 & 11 outlets - 32 mm or 38 mm diameter |
| OPTIONAL EQUIPMENT: | Hose, head and boot kits to suit most cultivators. Small Seeds Box. Liquid Tank (on 3 bin models only). Rear mounted tow bar for towing harrows or prickle chains. Loading auger (200 mm diameter). Wing Cut-Off (allows seeding to occur only through the centre frame). Load Cells (to measure inputs of bin contents accurately). Work Light Kit. |