

## Specifications

	<b>Centre Frame</b>
<b>Narrow Centre</b>	11' 10" (3.6m)
<b>Medium Centre</b>	13' 0" (4.0m)
<b>Standard Centre</b>	17' 9" (5.4m)

### NUMBER OF TINES

At 7" (180mm) spacings
At 8 3/4" (225mm) spacings
At 10 1/2" (270mm) spacings
At 10" (250mm) spacings
At 12" (300mm) spacings

### FRAME DIMENSIONS

Height (transport)	
Width (transport)	
Length	A Frame Length
	Main Frame Depth
	Total Length

### WEIGHT (at 7" tine spacing) kg

### TYRES Centre Frame and Wings

### KEY MEASUREMENTS

Underframe Clearance
Undertine Clearance
Road Transport Clearance
Working Depth

### TINE BREAKOUT

Spring Tine – Light Spring
– Standard Spring
– Dual Spring
Hydraulic Tine

## Controlled Traffic Scaribars

	Single Fold 2m Tracks		Single Fold 3m Tracks	
	20' (6.0m) 3 beds	26' (8.0m) 4 beds	29' (9.0m)	39' (12.0m) 3 beds
	27	37	47	63
	21	29	37	49
	15	N/A	30	40
	10' 0" (3.1m)	12' 6" (3.8m)	14' 3" (4.3m)	17' 3" (5.3m)
	17' 7" (5.4m)	17' 7" (5.4m)	18' 11" (5.8m)	18' 11" (5.8m)
	16' 0"	16' 0"	16' 0"	16' 0"
	11' 6"	11' 6"	11' 6"	11' 6"
	27' 6" (8.4m)	27' 6" (8.4m)	27' 6" (8.4m)	27' 6" (8.4m)
	4,600	5,200	6,000	6,600

← 15.5/80 x 24 →

(common to all machines)

28"	(710mm)
23"	(575mm)
11 1/4"	(285mm)
6"	(150mm)

	Low setting	Medium setting	High setting
	70lb (30kg)	105lb (47kg)	145lb (65kg)
	165lb (74kg)	260lb (116kg)	350lb (157kg)
	235lb (104kg)	365lb (163kg)	485lb (216kg)
	75lb (35kg)	→ 660lb (300kg)	



2m Scaribar with matching A-frame mounted Airseeder