

Medium Centre

Fixed Frame Scaribar

		Medium Centre			
Centre Frame					
Medium Centre	13' 0" (4.0m)	12' (3.8m)	14' (4.1m)	17' (5.2m)	20' (5.9m)
NUMBER OF TINES (set on 5 rows)					
At 7" (180mm) spacings	19	21	27	21	
At 8 ³ / ₄ " (225mm) spacings		15	17	21	17
At 10 ¹ / ₂ " (270mm) spacings		12	14	18	14
FRAME DIMENSIONS					
Height (transport)		6' 10" (2.1m)	6' 10" (2.1m)	6' 10" (2.1m)	6' 10" (2.1m)
Width (transport)		11' 3" (3.4m)	12' 4" (3.8m)	16' 1" (4.9m)	12' 5" (3.8 m)
Length	A Frame Length	16' 0"	16' 0"	16' 0"	
	Main Frame Depth	11' 6"	11' 6"	11' 6"	
	Total Length	27' 6" (8.4m)	27' 6" (8.4m)	27' 6" (8.4m)	27' 6" (8.4m)
WEIGHT (at 7" tine spacing) kg		3,000	3,100	3,600	3200
TYRES					
Centre Frame and Wings Floating Hitch (Front)		← 15.5/80 x 24 →			
KEY MEASUREMENTS					
Under Frame Clearance		28" (710mm)			
Under Tine Clearance		23" (575mm)			
Road Transport Clearance		11 ¹ / ₄ " (285mm)			
Working Depth		6" (150mm)			
TINE BREAKOUT					
Spring Tine –	Light Spring	70lb (30kg)	105lb (47kg)	145lb (65kg)	
	Standard Spring	165lb (74kg)	260lb (116kg)	350lb (157kg)	
	Dual Spring	235lb (104kg)	365lb (163kg)	485lb (216kg)	
Hydraulic Tine	75lb (35kg)	→ 660lb (300kg)			

