

Single Fold with Standard Centre

Folded Wing Scaribar

	Centre Frame	Single Fold with Standard Centre							
Narrow Centre	11' 10" (3.6m)					*		**	
Medium Centre	13' 0" (4.0m)	33' (9.9m)	36' (11.0m)	37' (11.3m)	41' (12.4m)	42' (12.8m)	46' (13.9m)	47' (14.3m)	
Standard Centre	17' 9" (5.4m)								
NUMBER OF TINES (set on 5 rows)									
At 7" (180mm) spacings		55	61	63	69	71	77	79	
At 8 ³ / ₄ " (225mm) spacings		45	49	51	55	57	63	63	
At 10 ¹ / ₂ " (270mm) spacings		37	41	43	45	47	53	53	
FRAME DIMENSIONS									
Height (transport)		12' 1" (3.7m)	13' 7" (4.1m)	14' 6" (4.4m)	15' 11" (4.8m)	16' 5" (5.0m)	18' 10" (5.7m)	18' 10" (5.7m)	
Width (transport)		23' 6" (7.2m)	23' 6" (7.2m)	23' 6" (7.2m)	23' 6" (7.2m)	23' 6" (7.2m)	23' 6" (7.2m)	23' 6" (7.2m)	
Length	A Frame Length	16' 0"	16' 0"	16' 0"	16' 0"	16' 0"	16' 0"	16' 0"	
	Main Frame Depth	11' 6"	11' 6"	11' 6"	11' 6"	11' 6"	11' 6"	11' 6"	
	Total Length	27' 6"	27' 6"	27' 6"	27' 6"	27' 6"	27' 6"	27' 6"	
WEIGHT (at 7" tine spacing) kg									
		6,300	6,500	6,600	7,100	7,700	8,300	8,400	
TYRES									
Centre Frame and Wings		← 15.5/80 x 24 →							
Floating Hitch (Front)						10.5/80x18 (6 off)	10.5/80x18 (6 off)		



KEY MEASUREMENTS (common to all machines)

Under Frame Clearance	28"	(710mm)
Under Tine Clearance	23"	(575mm)
Road Transport Clearance	11 ¹ / ₄ "	(285mm)
Working Depth	6"	(150mm)

TINE BREAKOUT	Low setting	Medium setting	High setting
Spring Tine – Light Spring	70lb (30kg)	105lb (47kg)	145lb (65kg)
Standard Spring	165lb (74kg)	260lb (116kg)	350lb (157kg)
Dual Spring	235lb (104kg)	365lb (163kg)	485lb (216kg)
Hydraulic Tine	75lb (35kg)	→ 660lb (300kg)	

- * Floating Hitch option available
- ** Floating Hitch model only