

Specifications

	Centre Frame
Narrow Centre	11' 10" (3.6m)
Medium Centre	13' 0" (4.0m)
Standard Centre	17' 9" (5.4m)

NUMBER OF TINES

At	7" (180mm) spacings
At	8 ³ / ₄ " (225mm) spacings
At	10 ¹ / ₂ " (270mm) spacings
At	10" (250mm) spacings
At	12" (300mm) spacings

FRAME DIMENSIONS

Height	(transport)
Width	(transport)
Length	A Frame Length Main Frame Depth Total Length

WEIGHT (at 7" tine spacing) kg

TYRES Centre Frame and Wings

KEY MEASUREMENTS

Underframe Clearance	28" (710mm)
Undertine Clearance	23" (575mm)
Road Transport Clearance	11 ¹ / ₄ " (285mm)
Working Depth	6" (150mm)

TINE BREAKOUT

Spring Tine – Light Spring	70lb (30kg)
– Standard Spring	165lb (74kg)
– Dual Spring	235lb (104kg)
Hydraulic Tine	75lb (35kg)

Precision Seeding System Scaribars

Single Fold				Double Fold			
23'	27'						
		32'	36'				
				43'	47'	55'	63'

28	32	38	44	51	55	65	73
23	27	32	36	43	47	55	63

10'8"	12'1"	13'3"	15'4"	16'5"	18'10"	14'9"	16'9"
(3.2m)	(3.7m)	(4.0m)	(4.7m)	(5.0m)	(5.7m)	(4.5m)	(5.1m)
18'11"	18'11"	18'11"	18'11"	18'11"	18'11"	23'6"	23'6"
(5.8m)						(7.2m)	(7.2m)
16'0"	16'0"	16'0"	16'0"	16'0"	16'0"	20'8"	20'8"
14'4"	14'4"	14'4"	14'4"	14'4"	14'4"	14'4"	14'4"
30'0"	30'0"	30'0"	30'0"	30'0"	30'0"	34'9"	34'9"
(9.1m)	(9.1m)	(9.1m)	(9.1m)	(9.1m)	(9.1m)	(10.6m)	(10.6m)
5,800	6,300	7,000	7,600	9,000	9,700	12,500	13,300

← 15.5/80 x 24 →

(common to all machines)

28"	(710mm)
23"	(575mm)
11 ¹ / ₄ "	(285mm)
6"	(150mm)

	Low setting	Medium setting	High setting
Spring Tine – Light Spring	70lb (30kg)	105lb (47kg)	145lb (65kg)
– Standard Spring	165lb (74kg)	260lb (116kg)	350lb (157kg)
– Dual Spring	235lb (104kg)	365lb (163kg)	485lb (216kg)
Hydraulic Tine	75lb (35kg)		660lb (300kg)

