

## Tow Behind (Trailed)

		Two Bin	
MODEL		4000	6000
-bin splits	litres	2000/2000	2600/3400
<b>CAPACITY:</b>			
-all wheat	(x 0.78) (kg)	3120	4680
-all fertiliser	(x 1.0) (kg)	4000	6000
-wheat/fertiliser	(kg)	1560/2000	2030/3400
-wheat/fertiliser/urea	(x 0.76) (kg)	n/a	n/a
<b>SMALL SEEDS BOX OPTION</b>	(litres)	280	520
<b>METERING OUTLETS PER BIN:</b>			
- Single Shoot	No. x diam(mm)	6 x 64	8 x 64
- Double Shoot	No. x diam(mm)	3 x 64	4 x 64
<b>NO. OF SOWING OUTLETS:</b>			
- Single Shoot	- min	15	20
	- max	66	88
- Double Shoot	- min	2 x 15	2 x 20
	- max	2 x 66	2 x 88
<b>DIMENSIONS:</b>			
- Ground Clearance	(m)	0.45	0.45
- Length	(m)	6.85	7.08
- Width	(m)	2.52	2.95
- Height (to fill)	(m)	2.57	2.75
<b>WEIGHT EMPTY (APPROX)</b>	(kg)	1500	2000
<b>TYRES:</b>			
- Front		n/a	n/a
- Rear		5.5/80 x 24	18.4 x 30
		18.4 x 30 (opt)	
<b>WHEEL TRACK</b>	- front (m)	n/a	n/a
	- rear (m)	2.0	2.59
		2.00/2.20 (opt)	2.00 (opt)



<b>METERING DRIVE SYSTEM</b>	Electric variable drive or ground driven spur gear
<b>MATERIAL SOWING CAPACITY</b>	Up to 5 tonnes per hour maximum sowing capacity - depending on model
<b>PRIMARY HOSE DIAMETER</b>	64 mm
<b>DISTRIBUTION HEADS:</b>	
- Single (64 mm inlet)	5, 6, 7, 8, 9, 10 & 11 outlets - 32 mm or 38 mm diameter
- Single (44.5 mm inlet)	5, 6, 7, 8, 9, 10 & 11 outlets - 32 mm or 38 mm diameter
<b>OPTIONAL EQUIPMENT:</b>	
	Hose, head and boot kits to suit most cultivators.
	Small Seeds Box.
	Liquid Tank (on 3 bin models only).
	Rear mounted tow bar for towing harrows or prickle chains.
	Loading auger (200 mm diameter).
	Wing Cut-Off (allows seeding to occur only through the centre frame).
	Load Cells (to measure inputs of bin contents accurately).
	Work Light Kit.